

CHATTAHOOCHEE SEALER

USES

- ★ Seal, protect, and add gloss to epoxy-set (Chattahoochee) stone.

DESCRIPTION

CHATTAHOOCHEE SEALER is a tough, high solids acrylic concrete sealer in a solvent base. It is designed to protect and beautify epoxy-set (Chattahoochee) stone with a high gloss, durable clear coating. CHATTAHOOCHEE SEALER is non-yellowing under sun exposure.

TOOLS REQUIRED

Use brush for cutting in tight spots and long nap roller for epoxy-set stone. Use metal or heavy duty plastic container. A solvent-resistant pump sprayer may be used.

PREPARATION

Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or similar oil based sealer or stain. Make sure the surface is clean, dry and sound. Clean oily concrete with EAGLE CONCRETE CLEANER DEGREASER NEUTRALIZER or other degreasing soap. Use a bristle brush for heavily oiled spots. Allow 24 hours to dry. Apply only when surface and air temperatures are above 50° F and below 90° F. Do not apply to excessively hot surfaces as rapid drying may cause bubbles to form.

APPLICATION

Brush may be used where roller won't reach. Do not pour directly from can to concrete. Apply evenly from can, metal or heavy duty plastic container with appropriate roller. Use a long nap roller for epoxy-set stone. Keep roller soaked by dipping on every stroke. Every few feet turn perpendicular to the first coat and cross roll without re-dipping. Ensure surface is tack-free before applying a second coat. Continual dipping on the first coat gives a heavy film and cross-rolling allows for an even film thickness. If spraying, use a metal container and clean immediately with mineral spirits. Suitable for light foot traffic in 6 hours. May be driven on in approximately 48 hours. Cooler temperatures and/or high humidity will increase drying time. Overly thick application will increase dry time. One coat, if applied at proper rate, is all that is needed. Cross roll in perpendicular direction to ensure even application. Two thin coats combining to give the proper coverage rate may have better results. Typically dries for re-coat in 3 hours.

NET COVERAGE RATE

100 ft² per gallon over epoxy set stone.

LIMITATIONS

Not aesthetically recommended for unsealed broom-finished (plain) concrete. Sealer may melt plastic, asphalt, or any petroleum-based product. Any surfaces not mentioned should be tested in small areas before applying sealer. NOTE: Gasoline and other Auto parts cleaners containing hot solvents will melt film. Wiping will smear the coating. Allow to dry. Either leave for protection or re-coat with for best appearance. It is highly recommended that you test an inconspicuous spot before proceeding with whole floor.

MAINTENANCE

Clean sealed surface with water only. Reseal surface as needed, but no more often than every two years to prevent buildup of sealer.

WARNING

COMBUSTIBLE. EYE, SKIN & RESPIRATORY IRRITANT. Contains Aromatic Naptha. Do not use near heat, sparks or open flames. Avoid contact with eyes and prolonged contact with skin. Use only with adequate ventilation. Do not inhale vapors. Do not ingest. See Safety Data Sheet for more info.

FIRST AID

In case of eye contact, flush with water for 15 minutes. In case of skin contact, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Immediately contact hospital ER or physician. If vapors are inhaled or breathing becomes difficult, move person to fresh air. Seek medical attention if skin, eye or respiratory irritation persists. See Safety Data Sheet for more info.

TECHNICAL DATA

VOC: <600g/L Flash Point: 105° F

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Eagle IFP warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.

Made in U.S.A
EAGLE IFP COMPANY
www.eaglesealer.com